

## Product information | TECHNICAL DATA SHEET

### SEAL-COATING.

400 ml, 10.68 Oz, 303 g.

#### GENERAL DESCRIPTION

Paint with an elastic base ideal for sealing or repairing waterproof interior or exterior surfaces such as roofs, coverings, plastic metal pipes and any other type of PVC pipe. Create a waterproof and flexible layer that protects and waterproofs all types of surfaces.

#### CHARACTERISTICS

- Fast-drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Excellent adhesion on porous surfaces.
- Excellent weather resistance.
- High sealing and waterproofing potential.
- High opacity.

#### APPLICATION

Due to the characteristics of the product, we recommend its use for the sealing, protection and waterproofing of horizontal and vertical surfaces both indoors and outdoors.

- Terraces, balconies, roofs.
- Metal or plastic pipes (drains, PVC pipes).
- Waterproofing of wet areas. (ponds, aquariums)
- Inside stone, ceramic or wooden plant pots, etc.

#### INSTRUCTIONS FOR USE

- Prepare and properly clean the area to be sealed before applying the product, to ensure effective adhesion.
- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply the product on the area you wish to repair and around it at a distance of 20-30 cm. Apply two or three coats for best results. Depending on the size of the crack, more coats may be necessary.
- Repaint after 20-30' minutes with the same paint.
- Invert the spray can to purge the valve after use. If the cap becomes clogged replace it with a new one.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
- Request safety data sheets.

#### GENERAL DESCRIPTION

Binder type:	Special resin
Color:	Black, teak red y white
Dry to the touch (ASTM D-1640 ISO 1517):	30-45'
Total dry time (ASTM D-1640 ISO 1517):	24 h (2 coats)
Thickness of dry coat (ASTM D-823 ISO 2808):	30 µ/coat
Adherence (ASTM D-3359 ISO 2409):	No aplica
Repainted*:	30'
Repainted with other paints*:	24h
Theoretical performance (continuous painting):	1-1,25 m <sup>2</sup> ; 2 coats (60 µ) 0,6-0,75 m <sup>2</sup>
Shelf life:	5 años. (Correctly stored)
Condiciones de aplicacion:	Atmospheric temp. 10-35°C
	Surface temp. 5°-50 C
	Max. Humidity. 85% R.H.P

\* Times may vary depending on thickness of coat.

150421

#### IMAGE



#### LABEL



#### CAP SYSTEM



Negro / Black  
EX014PIM002

Blanco / White  
EX014PIM001

Rojo / Red  
EX014PIM003

#### PACKAGING

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm

